

BIG BIKE PARTS® INSTALLATION INSTRUCTIONS

Copyright© 2008 by Big Bike Parts, Inc. No part of this instruction sheet may be reproduced without the written permission of Big Bike Parts, Inc.

PART NO. 17-990, 17-952C, 17-953, 17-954, 17-955C

HEATED GRIPS CRUISERS, SPORT BIKES, SCOOTERS, ATVS & SNOWMOBILES

04/18/08

ITEMS NEEDED: KNIFE SANDPAPER CLEANING SOLVENT GRIP GLUE

1. REMOVE HANDLEBAR WEIGHTS, IF APPLICABLE. REMOVE OLD GRIPS BY EITHER CUTTING THEM OFF OR TWISTING THEM OFF. SOME BIKES WITHOUT WEIGHTS HAVE CHROME CAPS THAT NEED TO BE SCREWED OR PRIED OFF.
2. CLEAN THE HANDLEBAR AND THROTTLE TUBE (IF APPLICABLE) OF ANY REMAINING GLUE LEFT BEHIND FROM THE OLD GRIP. WITH ALL THE GLUE REMOVED, LIGHTLY ROUGH THE SURFACE UP WITH SANDPAPER AND THEN CLEAN THE SURFACE WITH A MILD SOLVENT.
3. APPLY GRIP GLUE TO INSIDE OF GRIPS. A BEAD OF GLUE NEEDS TO BE PLACED AROUND THE ENTIRE INSIDE DIAMETER. AS THE GRIPS ARE SLID ONTO THE HANDLEBARS, IT WILL SPREAD THE GLUE ALONG THE LENGTH OF THE GRIP. DO NOT PLACE GRIP GLUE DIRECTLY ON THE HANDLEBAR; THE GRIP WILL PUSH IT TOWARDS THE SWITCH BOX AND CREATE A MESS.
4. INSTALL THE GRIPS ON THE BIKE WITH THE WIRES FROM THE GRIPS FACING FORWARD OR DOWNWARD. MAKE SURE THERE IS ENOUGH SLACK ON THE THROTTLE SIDE FOR MOVEMENT OF THE THROTTLE ITSELF.
5. WIRE THE FUSED WIRE HARNESS TO THE BATTERY, LOCATED UNDER EITHER THE SEAT OR A SIDE COVER. (RED GOES TO POSITIVE, BLACK GOES TO NEGATIVE). ATTACH THE TEMPERATURE CONTROLLER TO THE HANDLEBARS ON WHICHEVER SIDE IS MORE COMFORTABLE. LEFT SIDE INSTALLATION IS PREFERRED TO ADJUST THE TEMPERATURE WHILE RIDING. IF YOU HAVE A SCOOTER, SPORT BIKE, ATV OR SNOWMOBILE YOU MAY ATTACH IT TO A FLAT SURFACE.
6. CONNECT THE TEMPERATURE CONTROLLER TO THE FUSED WIRE HARNESS AND THE GRIPS TO THE TEMPERATURE CONTROLLER. IF NEEDED, USE ZIP TIES (NOT INCLUDED) TO KEEP THE WIRES OUT OF THE WAY. THE CONNECTION SHOULD BE ROUTED TO THE HEADLIGHT OR SOMEWHERE OUT OF THE WEATHER.
7. TEST FOR FUNCTION AND REINSTALL HANDLEBAR WEIGHTS, IF APPLICABLE. IT WILL TAKE THE GRIPS A FEW MINUTES TO WARM UP TO FULL TEMPERATURE WHEN TURNED ON.